



HYUNDAI

ST-TM17D

www.hyundai.it

info@hyundai.it

Code		0170119
LCD Panel	Active Area	337.9mm (H) x 270.34mm (V) (17.0" diagonal)
	Driver Element	a-si TFT Active Matrix
	Pixel Number	1280 x R.G.B. x 1024 pixel
	Pixel Pitch	0.264mm (H) x 0.264mm (V)
	Pixel Arrangement	RGB Vertical Stripe
	Display Color	16.2M color
	Viewing Angle (H / V)	160 / 120 degree
	Brightness	350 cd/m ²
	Contrast Ratio	350
	Response Time (Tr+Tf)	14 msec
Graphic	Separate Sync.	TTL Level
	Horizontal Sync.	Positive / Negative
	Vertical Sync.	Positive / Negative
	Input Connector	D-Sub 15 pins
Performance	Auto Adjust	Clock, Phase, H Position & V Position
	Screen Scaling	VGA/SVGA/XGA/SXGA Full Screen Display
	Power Management	VESA DPMS, ENERGY STAR ® Compliance
	Color Adjustment	User, 6500K, 7500K & 9300K
	OSD Language	English, French, German, Spanish, Italian, Japanese, Traditional Chinese, Simplified Chinese, Russian
Power source	Power Input	AC100~240 (Worldwide) V
	Power Output	19 Vdc
Power consumption	Operation Mode	51 W
	Power Saving Mode	< 3 W
Physical	Dimension	387mm (W) x 204mm (D) x 408mm (H)
Physical	Weight	3.5 kg
DDC	Plug & Play	DDC 2B Compliance
Function	OSD key	6 key
	Turbo (Brightness Switch)	Picture Mode: 350 cd/m ² Text Mode: 200 cd/m ² Economy Mode: 140 cd/m ²
	Audio	2.5W ch
	Touch Panel	Resistive Technology
Warranty	Type	Two Years On Center
Options	-	-

H.I.I. S.p.A.

Le caratteristiche citate possono variare senza preavviso anche a causa di errori tipografici e/o omissioni.